


NN06090115EU

FIBERGLASS TANK





NOTES:
 - GENERIC DRAWING FOR REFERENCE ONLY
 - SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019			
TOLERANCES (LINEAR)				 GRANBY COMPOSITES				Revision description					
FEET DIM. -> ± 1% 0.0 -> ± 0.5"								0.00 -> ± 0.25" 0.000 -> ± 0.125"					
TOLERANCES (ANGULAR)				Drawn by O. Marin				Format B		Part no. NN06090115EU		REV 02.	
0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.								20/12/2023					
Weight : 1454 Lb				Approved by :				Title					
								6' Dia. TANK - 3076 US gal					
Client				# Project				Sheet 1 / 4					

Item	Part Number	Qty	Description	Check List
1	ADF0000001	1	FOAM 28-3/4" DIA. x 8" / R-35	
2	ADPGILP001	2	LIFTING LUGS	
3	ENSCOUR6	1	ANCHORING KIT	
4	EV480	1	4" SCH. 80 VENT KIT WITH SST BIRD SCREEN	
5	GMHE30-COVER01	1	30" DIA. FRP. - LOCKABLE MAN HOLE COVER WITH HINGE	
6	MH-30 (6"L.)	1	30" DIA. x 6" L. - MANHOLE	
7	MHE-30 (54"L.)	1	30" DIA. x 54" L. - MANHOLE EXTENSION	
8	PFV01414	1	0.5" x 13.5" x 13.5" ANTI-VORTEX PLATE	
9	TP80400G01 (4.25"L.)	1	4" SCH.80 GREY PVC PIPE	
10	TP80400G01 (36"L.)	2	4" SCH.80 GREY PVC PIPE	

BACKFILL PROPERTIES
N1 - 1/8" TO 3/4" PEA GRAVEL OR 1/2" CRUSHED STONE
N2 - PRIMARY BACKFILL, 1/8" TO 3/4" PEA GRAVEL OR 1/2" CRUSHED STONE
N3 - SECONDARY BACKFILL, COARSE SAND OR GRAVEL 1 1/2" OR LESS



SECTION ELEVATION VIEW


Optional anchoring depending on the tank's environment

- Technical informations**
- Burrial depth: According to the geotechnical installation conditions
 - Inside Diameter : 72"
 - (If required) Quantity of fiberglass anchoring straps : 2
 - (If required) Quantity of reinforced concrete deadman anchors : 4
 - Simultaneous lifting by 2 lugs. The angle of the (chains or belts, etc.) must not be less than 60° from the horizontal
 - The weight on the drawing does not include kits of belts and concrete blocks.
 - HS-20 rated for burial depth from 36 to 84 inches
 - Manufactured according to ANSI-AWWA D120 requirements
 - Airtightness test performed at the factory at 5psig

The tank must be installed in accordance with the manufacturer's instructions.

NOTES:
- GENERIC DRAWING FOR REFERENCE ONLY
- SHOP DRAWING AVAILABLE ON REQUEST



This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019							
TOLERANCES (LINEAR)				 GRANBY COMPOSITES				Revision description									
FEET DIM. -> ± 1% 0.0 -> ± 0.5"								0.00 -> ± 0.25" 0.000 -> ± 0.125"									
TOLERANCES (ANGULAR)				Drawn by O. Marin				Format B				Part no. NN06090115EU				REV 02.	
0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.								0.00 -> ± 0.1 DEG.				Title 6' Dia. TANK - 3076 US gal					
Weight : 1454 Lb				Approved by :													
Client				# Project				Sheet 2 / 4									




PLAN VIEW

NOTES:
- GENERIC DRAWING FOR REFERENCE ONLY
- SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019	
TOLERANCES (LINEAR)						Revision description					
FEET DIM. -> ± 1%						Format		Part no.		REV	
0.0 -> ± 0.5"						B		NN06090115EU		02.	
0.00 -> ± 0.25"											
0.000 -> ± 0.125"											
TOLERANCES (ANGULAR)			Drawn by O. Marin			20/12/2023					
0 -> ± 2 DEG.											
0.0 -> ± 0.5 DEG.			0.00 -> ± 0.1 DEG.								
Weight :			Approved by :					Title			
1454 Lb								6' Dia. TANK - 3076 US gal			
Client		# Project			Sheet						
					3 / 4						



ITEM : ENSCOUR6



Fiberglass Strap Guide
Directly installed on the tank

- Turnbuckle**
- Forged carbon steel, hot-dip galvanized
 - In accordance with US specifications FF-T-791B Type 1, Form 1 (open cage).
 - Safety factor 5:1
 - Working load 5,200 Lbs
- Concrete deadman anchor**
- Weight : 1,093 Lbs
 - Reinforced with galvanized steel
- Fiberglass strap**
- High quality fiberglass
 - Working load 20,000 Lbs
 - Ultimate rated 45,000 Lbs
 - Equipped with galvanized steel rings

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019			
TOLERANCES (LINEAR)								Revision description					
FEET DIM. -> ± 1%								Format		Part no.		REV	
0.0 -> ± 0.5"								B		ENSCOUR6		A.	
TOLERANCES (ANGULAR)				Drawn by				04/10/2018					
0 -> ± 2 DEG.				O. Marin									
0.0 -> ± 0.5 DEG.				0.00 -> ± 0.125"				Title					
Weight :				Approved by :				ANCHORING KIT					
Client				# Project				Sheet					
								4 / 4					



CAPACITY CHART FOR NN06090115 TANK

Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)
66	2970	67	2996	68	3019	69	3040	70	3056	71	3069										
66 1/8	2974	67 1/8	2999	68 1/8	3022	69 1/8	3042	70 1/8	3058	71 1/8	3070										
66 1/4	2977	67 1/4	3002	68 1/4	3025	69 1/4	3044	70 1/4	3060	71 1/4	3071										
66 3/8	2980	67 3/8	3005	68 3/8	3027	69 3/8	3046	70 3/8	3062	71 3/8	3073										
66 1/2	2984	67 1/2	3008	68 1/2	3030	69 1/2	3049	70 1/2	3063	71 1/2	3073										
66 5/8	2987	67 5/8	3011	68 5/8	3032	69 5/8	3051	70 5/8	3065	71 5/8	3074										
66 3/4	2990	67 3/4	3014	68 3/4	3035	69 3/4	3053	70 3/4	3066	71 3/4	3075										
66 7/8	2993	67 7/8	3017	68 7/8	3037	69 7/8	3055	70 7/8	3068	71 7/8	3075										

** PRECISION IS ABOUT +/- 1%