


NN10210791EP

FIBERGLASS TANK



NOTES:
 - GENERIC DRAWING FOR REFERENCE ONLY
 - SHOP DRAWING AVAILABLE ON REQUEST



This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.						2019
TOLERANCES (LINEAR)		 GRANBY COMPOSITES		Revision description		
FEET DIM. -> ±1% 0.0 -> ±0.5"				Format B		
0.00 -> ±0.25" 0.000 -> ±0.125"		Part no. NN10210791EP		REV 02.		
TOLERANCES (ANGULAR)		Drawn by O. Marin		19/12/2023		
0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.		Approved by :		Title		
Weight : 5784 Lb				10' Dia. TANK - 20882 US gal		
Client		# Projet		Sheet 1 / 4		

Item	Part Number	Qty	Description	Check List
1	ADF0000001	1	FOAM 28-3/4" DIA. x 8" / R-35	
2	ADP0000001	2	LIFTING LUG	
3	ENSCOUR10	5	ANCHORING KIT	
4	EV480	1	4" SCH. 80 VENT KIT WITH SST BIRD SCREEN	
5	GMHE30-COVER01	1	30" DIA. FRP. - LOCKABLE MAN HOLE COVER WITH HINGE	
6	MH-30 (6"L.)	1	30" DIA. x 6" L. - MANHOLE	
7	MHE-30 (54"L.)	1	30" DIA. x 54" L. - MANHOLE EXTENSION	
8	PFV01414	1	0.5" x 13.5" x 13.5" ANTI-VORTEX PLATE	
9	TP80400G01 (4.25"L.)	1	4" SCH.80 GREY PVC PIPE	
10	TP80400G01 (42"L.)	2	4" SCH.80 GREY PVC PIPE	

BACKFILL PROPERTIES

- N1 - 1/8" TO 3/4" PEA GRAVEL OR 1/2" CRUSHED STONE
N2 - PRIMARY BACKFILL, 1/8" TO 3/4" PEA GRAVEL OR 1/2" CRUSHED STONE
N3 - SECONDARY BACKFILL, COARSE SAND OR GRAVEL 1 1/2" OR LESS

OPTIONAL INSULATION FOAM



Optional anchoring depending on the tank's environment

Technical informations


- Burrial depth: According to the geotechnical installation conditions
- Inside Diameter : 120" "
- (If required) Quantity of fiberglass anchoring straps : 5
- (If required) Quantity of reinforced concrete deadman anchors : 10
- Simultaneous lifting by 2 lugs. The angle of the (chains or belts, etc.) must not be less than 60° from the horizontal
- The weight on the drawing does not include kits of belts and concrete blocks.
- HS-20 rated for burial depth from 36 to 84 inches
- Manufactured according to ANSI-AWWA D120 requirements
- Manufactured according to NSF-61 requirements for drinking water
- Airtightness test performed at the factory at 35 kPa

The tank must be installed in accordance with the manufacturer's instructions.

SECTION ELEVATION VIEW

- NOTES:
- GENERIC DRAWING FOR REFERENCE ONLY
 - SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.					2019	
TOLERANCES (LINEAR) FEET DIM. -> ± 1% 0.0 -> ± 0.5"		 GRANBY COMPOSITES	Revision description			
TOLERANCES (ANGULAR) 0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.		Drawn by O. Marin	19/12/2023	Format B	Part no. NN10210791EP	REV 02.
Weight : 5784 Lb				Approved by :	Title 10' Dia. TANK - 20882 US gal	
Client	# Project	Sheet 2 / 4				



PLAN VIEW

NOTES:
- GENERIC DRAWING FOR REFERENCE ONLY
- SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019
TOLERANCES (LINEAR) FEET DIM. -> ± 1% 0.0 -> ± 0.5"0.00 -> ± 0.25" 0.000 -> ± 0.125"			GRANBY COMPOSITES Drawn by O. Marin Approved by :			Revision description				
						Format B	Part no. NN10210791EP		REV 02.	
TOLERANCES (ANGULAR) 0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.0.00 -> ± 0.1 DEG.			19/12/2023			Title 10' Dia. TANK - 20882 US gal				
Weight : 5784 Lb										
Client		# Project			Sheet 3 / 4					



Fiberglass Strap Guide
Directly installed on the tank

- Turnbuckle**
- Forged carbon steel, hot-dip galvanized
 - In accordance with US specifications FF-T-791B Type 1, Form 1 (open cage).
 - Safety factor 5:1
 - Working load 5,200 Lbs
- Concrete deadman anchor**
- Weight : 1,093 Lbs
 - Reinforced with galvanized steel
- Fiberglass strap**
- High quality fiberglass
 - Working load 20,000 Lbs
 - Ultimate rated 45,000 Lbs
 - Equipped with galvanized steel rings

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019
TOLERANCES (LINEAR)						Revision description				
FEET DIM. -> ± 1% 0.0 -> ± 0.5"										
0.00 -> ± 0.25" 0.000 -> ± 0.125"						Format B		Part no. ENSCOUR10		REV A.
TOLERANCES (ANGULAR)			Drawn by O. Marin			04/10/2018			Title ANCHORING KIT	
0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.										
0.00 -> ± 0.1 DEG.			Approved by :							
Weight :										
Client		# Projet			Sheet 4 / 4					



CAPACITY CHART FOR NN10210791 TANK

Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)
-		6	346	12	993	18	1834	24	2823	30	3929	36	5127	42	6396	48	7716	54	9070	60	10441
1/8	1	6 1/8	357	12 1/8	1009	18 1/8	1853	24 1/8	2845	30 1/8	3953	36 1/8	5153	42 1/8	6423	48 1/8	7744	54 1/8	9099	60 1/8	10470
1/4	3	6 1/4	368	12 1/4	1025	18 1/4	1873	24 1/4	2867	30 1/4	3977	36 1/4	5179	42 1/4	6450	48 1/4	7772	54 1/4	9127	60 1/4	10498
3/8	6	6 3/8	379	12 3/8	1041	18 3/8	1892	24 3/8	2889	30 3/8	4002	36 3/8	5204	42 3/8	6477	48 3/8	7800	54 3/8	9156	60 3/8	10527
1/2	8	6 1/2	391	12 1/2	1057	18 1/2	1911	24 1/2	2911	30 1/2	4026	36 1/2	5230	42 1/2	6504	48 1/2	7828	54 1/2	9184	60 1/2	10556
5/8	12	6 5/8	402	12 5/8	1073	18 5/8	1931	24 5/8	2933	30 5/8	4050	36 5/8	5256	42 5/8	6531	48 5/8	7856	54 5/8	9213	60 5/8	10584
3/4	15	6 3/4	414	12 3/4	1089	18 3/4	1950	24 3/4	2956	30 3/4	4074	36 3/4	5282	42 3/4	6558	48 3/4	7884	54 3/4	9241	60 3/4	10613
7/8	19	6 7/8	426	12 7/8	1105	18 7/8	1970	24 7/8	2978	30 7/8	4099	36 7/8	5308	42 7/8	6585	48 7/8	7912	54 7/8	9270	60 7/8	10642
1	23	7	438	13	1121	19	1990	25	3000	31	4123	37	5334	43	6613	49	7940	55	9298	61	10670
1 1/8	28	7 1/8	449	13 1/8	1138	19 1/8	2009	25 1/8	3023	31 1/8	4147	37 1/8	5360	43 1/8	6640	49 1/8	7968	55 1/8	9327	61 1/8	10699
1 1/4	32	7 1/4	462	13 1/4	1154	19 1/4	2029	25 1/4	3045	31 1/4	4172	37 1/4	5386	43 1/4	6667	49 1/4	7996	55 1/4	9355	61 1/4	10727
1 3/8	37	7 3/8	474	13 3/8	1171	19 3/8	2049	25 3/8	3067	31 3/8	4196	37 3/8	5412	43 3/8	6694	49 3/8	8024	55 3/8	9384	61 3/8	10756
1 1/2	42	7 1/2	486	13 1/2	1187	19 1/2	2069	25 1/2	3090	31 1/2	4221	37 1/2	5438	43 1/2	6722	49 1/2	8052	55 1/2	9412	61 1/2	10785
1 5/8	48	7 5/8	498	13 5/8	1204	19 5/8	2089	25 5/8	3112	31 5/8	4245	37 5/8	5464	43 5/8	6749	49 5/8	8080	55 5/8	9441	61 5/8	10813
1 3/4	53	7 3/4	511	13 3/4	1221	19 3/4	2109	25 3/4	3135	31 3/4	4270	37 3/4	5491	43 3/4	6776	49 3/4	8108	55 3/4	9469	61 3/4	10842
1 7/8	59	7 7/8	523	13 7/8	1238	19 7/8	2129	25 7/8	3158	31 7/8	4295	37 7/8	5517	43 7/8	6804	49 7/8	8136	55 7/8	9498	61 7/8	10870
2	65	8	536	14	1255	20	2149	26	3180	32	4319	38	5543	44	6831	50	8164	56	9526	62	10899
2 1/8	72	8 1/8	549	14 1/8	1272	20 1/8	2169	26 1/8	3203	32 1/8	4344	38 1/8	5569	44 1/8	6858	50 1/8	8193	56 1/8	9555	62 1/8	10928
2 1/4	78	8 1/4	562	14 1/4	1289	20 1/4	2190	26 1/4	3226	32 1/4	4369	38 1/4	5595	44 1/4	6886	50 1/4	8221	56 1/4	9583	62 1/4	10956
2 3/8	85	8 3/8	575	14 3/8	1306	20 3/8	2210	26 3/8	3248	32 3/8	4393	38 3/8	5622	44 3/8	6913	50 3/8	8249	56 3/8	9612	62 3/8	10985
2 1/2	92	8 1/2	588	14 1/2	1323	20 1/2	2230	26 1/2	3271	32 1/2	4418	38 1/2	5648	44 1/2	6941	50 1/2	8277	56 1/2	9640	62 1/2	11013
2 5/8	99	8 5/8	601	14 5/8	1340	20 5/8	2251	26 5/8	3294	32 5/8	4443	38 5/8	5674	44 5/8	6968	50 5/8	8305	56 5/8	9669	62 5/8	11042
2 3/4	106	8 3/4	614	14 3/4	1358	20 3/4	2271	26 3/4	3317	32 3/4	4468	38 3/4	5701	44 3/4	6995	50 3/4	8334	56 3/4	9698	62 3/4	11071
2 7/8	113	8 7/8	628	14 7/8	1375	20 7/8	2292	26 7/8	3340	32 7/8	4493	38 7/8	5727	44 7/8	7023	50 7/8	8362	56 7/8	9726	62 7/8	11099
3	121	9	641	15	1393	21	2312	27	3363	33	4518	39	5754	45	7050	51	8390	57	9755	63	11128
3 1/8	128	9 1/8	655	15 1/8	1410	21 1/8	2333	27 1/8	3386	33 1/8	4543	39 1/8	5780	45 1/8	7078	51 1/8	8418	57 1/8	9783	63 1/8	11156
3 1/4	136	9 1/4	669	15 1/4	1428	21 1/4	2354	27 1/4	3409	33 1/4	4568	39 1/4	5807	45 1/4	7106	51 1/4	8446	57 1/4	9812	63 1/4	11185
3 3/8	144	9 3/8	682	15 3/8	1446	21 3/8	2374	27 3/8	3433	33 3/8	4593	39 3/8	5833	45 3/8	7133	51 3/8	8475	57 3/8	9840	63 3/8	11213
3 1/2	152	9 1/2	696	15 1/2	1464	21 1/2	2395	27 1/2	3456	33 1/2	4618	39 1/2	5860	45 1/2	7161	51 1/2	8503	57 1/2	9869	63 1/2	11242
3 5/8	161	9 5/8	710	15 5/8	1481	21 5/8	2416	27 5/8	3479	33 5/8	4643	39 5/8	5886	45 5/8	7188	51 5/8	8531	57 5/8	9898	63 5/8	11271
3 3/4	169	9 3/4	724	15 3/4	1499	21 3/4	2437	27 3/4	3502	33 3/4	4668	39 3/4	5913	45 3/4	7216	51 3/4	8560	57 3/4	9926	63 3/4	11299
3 7/8	178	9 7/8	739	15 7/8	1517	21 7/8	2458	27 7/8	3526	33 7/8	4694	39 7/8	5939	45 7/8	7244	51 7/8	8588	57 7/8	9955	63 7/8	11328
4	187	10	753	16	1536	22	2479	28	3549	34	4719	40	5966	46	7271	52	8616	58	9983	64	11356
4 1/8	196	10 1/8	767	16 1/8	1554	22 1/8	2500	28 1/8	3573	34 1/8	4744	40 1/8	5993	46 1/8	7299	52 1/8	8644	58 1/8	10012	64 1/8	11385
4 1/4	205	10 1/4	782	16 1/4	1572	22 1/4	2521	28 1/4	3596	34 1/4	4769	40 1/4	6019	46 1/4	7327	52 1/4	8673	58 1/4	10041	64 1/4	11413
4 3/8	214	10 3/8	796	16 3/8	1590	22 3/8	2543	28 3/8	3620	34 3/8	4795	40 3/8	6046	46 3/8	7354	52 3/8	8701	58 3/8	10069	64 3/8	11442
4 1/2	223	10 1/2	811	16 1/2	1609	22 1/2	2564	28 1/2	3643	34 1/2	4820	40 1/2	6073	46 1/2	7382	52 1/2	8729	58 1/2	10098	64 1/2	11470
4 5/8	233	10 5/8	825	16 5/8	1627	22 5/8	2585	28 5/8	3667	34 5/8	4845	40 5/8	6100	46 5/8	7410	52 5/8	8758	58 5/8	10126	64 5/8	11499
4 3/4	243	10 3/4	840	16 3/4	1645	22 3/4	2607	28 3/4	3690	34 3/4	4871	40 3/4	6126	46 3/4	7438	52 3/4	8786	58 3/4	10155	64 3/4	11527
4 7/8	252	10 7/8	855	16 7/8	1664	22 7/8	2628	28 7/8	3714	34 7/8	4896	40 7/8	6153	46 7/8	7465	52 7/8	8815	58 7/8	10184	64 7/8	11556
5	262	11	870	17	1683	23	2650	29	3738	35	4922	41	6180	47	7493	53	8843	59	10212	65	11584
5 1/8	272	11 1/8	885	17 1/8	1701	23 1/8	2671	29 1/8	3762	35 1/8	4947	41 1/8	6207	47 1/8	7521	53 1/8	8871	59 1/8	10241	65 1/8	11613
5 1/4	282	11 1/4	900	17 1/4	1720	23 1/4	2693	29 1/4	3785	35 1/4	4973	41 1/4	6234	47 1/4	7549	53 1/4	8900	59 1/4	10269	65 1/4	11641
5 3/8	293	11 3/8	916	17 3/8	1739	23 3/8	2714	29 3/8	3809	35 3/8	4999	41 3/8	6261	47 3/8	7577	53 3/8	8928	59 3/8	10298	65 3/8	11670
5 1/2	303	11 1/2	931	17 1/2	1758	23 1/2	2736	29 1/2	3833	35 1/2	5024	41 1/2	6288	47 1/2	7604	53 1/2	8956	59 1/2	10327	65 1/2	11698
5 5/8	314	11 5/8	946	17 5/8	1777	23 5/8	2758	29 5/8	3857	35 5/8	5050	41 5/8	6315	47 5/8	7632	53 5/8	8985	59 5/8	10355	65 5/8	11727
5 3/4	324	11 3/4	962	17 3/4	1796	23 3/4	2780	29 3/4	3881	35 3/4	5076	41 3/4	6342	47 3/4	7660	53 3/4	9013	59 3/4	10384	65 3/4	11755
5 7/8	335	11 7/8	977	17 7/8	1815	23 7/8	2801	29 7/8	3905	35 7/8	5101	41 7/8	6369	47 7/8	7688	53 7/8	9042	59 7/8	10413	65 7/8	11784

** PRECISION IS ABOUT +/- 1%



CAPACITY CHART FOR NN10210791 TANK

Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)
66	11812	71	12943	76	14051	81	15129	86	16164	91	17145	96	18059	101	18893	106	19628	111	20241	116	20696
66 1/8	11841	71 1/8	12971	76 1/8	14079	81 1/8	15155	86 1/8	16189	91 1/8	17168	96 1/8	18081	101 1/8	18912	106 1/8	19645	111 1/8	20255	116 1/8	20704
66 1/4	11869	71 1/4	12999	76 1/4	14106	81 1/4	15182	86 1/4	16214	91 1/4	17192	96 1/4	18103	101 1/4	18932	106 1/4	19662	111 1/4	20268	116 1/4	20713
66 3/8	11897	71 3/8	13027	76 3/8	14133	81 3/8	15208	86 3/8	16239	91 3/8	17216	96 3/8	18125	101 3/8	18952	106 3/8	19678	111 3/8	20281	116 3/8	20722
66 1/2	11926	71 1/2	13055	76 1/2	14161	81 1/2	15234	86 1/2	16264	91 1/2	17239	96 1/2	18146	101 1/2	18971	106 1/2	19695	111 1/2	20294	116 1/2	20730
66 5/8	11954	71 5/8	13083	76 5/8	14188	81 5/8	15261	86 5/8	16289	91 5/8	17263	96 5/8	18168	101 5/8	18990	106 5/8	19712	111 5/8	20308	116 5/8	20738
66 3/4	11983	71 3/4	13111	76 3/4	14215	81 3/4	15287	86 3/4	16314	91 3/4	17286	96 3/4	18190	101 3/4	19010	106 3/4	19728	111 3/4	20321	116 3/4	20746
66 7/8	12011	71 7/8	13138	76 7/8	14243	81 7/8	15313	86 7/8	16339	91 7/8	17310	96 7/8	18211	101 7/8	19029	106 7/8	19745	111 7/8	20333	116 7/8	20754
67	12039	72	13166	77	14270	82	15339	87	16364	92	17333	97	18233	102	19048	107	19761	112	20346	117	20762
67 1/8	12068	72 1/8	13194	77 1/8	14297	82 1/8	15366	87 1/8	16389	92 1/8	17357	97 1/8	18254	102 1/8	19067	107 1/8	19777	112 1/8	20359	117 1/8	20769
67 1/4	12096	72 1/4	13222	77 1/4	14324	82 1/4	15392	87 1/4	16414	92 1/4	17380	97 1/4	18276	102 1/4	19087	107 1/4	19794	112 1/4	20372	117 1/4	20777
67 3/8	12125	72 3/8	13250	77 3/8	14351	82 3/8	15418	87 3/8	16439	92 3/8	17403	97 3/8	18297	102 3/8	19106	107 3/8	19810	112 3/8	20384	117 3/8	20784
67 1/2	12153	72 1/2	13278	77 1/2	14378	82 1/2	15444	87 1/2	16464	92 1/2	17427	97 1/2	18318	102 1/2	19124	107 1/2	19826	112 1/2	20396	117 1/2	20791
67 5/8	12181	72 5/8	13306	77 5/8	14406	82 5/8	15470	87 5/8	16489	92 5/8	17450	97 5/8	18340	102 5/8	19143	107 5/8	19842	112 5/8	20409	117 5/8	20798
67 3/4	12210	72 3/4	13334	77 3/4	14433	82 3/4	15496	87 3/4	16514	92 3/4	17473	97 3/4	18361	102 3/4	19162	107 3/4	19858	112 3/4	20421	117 3/4	20804
67 7/8	12238	72 7/8	13361	77 7/8	14460	82 7/8	15522	87 7/8	16538	92 7/8	17496	97 7/8	18382	102 7/8	19181	107 7/8	19874	112 7/8	20433	117 7/8	20811
68	12266	73	13389	78	14487	83	15548	88	16563	93	17519	98	18403	103	19200	108	19889	113	20445	118	20817
68 1/8	12295	73 1/8	13417	78 1/8	14514	83 1/8	15574	88 1/8	16588	93 1/8	17542	98 1/8	18424	103 1/8	19218	108 1/8	19905	113 1/8	20457	118 1/8	20823
68 1/4	12323	73 1/4	13445	78 1/4	14541	83 1/4	15600	88 1/4	16612	93 1/4	17565	98 1/4	18445	103 1/4	19237	108 1/4	19921	113 1/4	20468	118 1/4	20829
68 3/8	12351	73 3/8	13473	78 3/8	14568	83 3/8	15626	88 3/8	16637	93 3/8	17588	98 3/8	18466	103 3/8	19255	108 3/8	19936	113 3/8	20480	118 3/8	20835
68 1/2	12379	73 1/2	13500	78 1/2	14595	83 1/2	15652	88 1/2	16662	93 1/2	17611	98 1/2	18487	103 1/2	19274	108 1/2	19951	113 1/2	20492	118 1/2	20840
68 5/8	12408	73 5/8	13528	78 5/8	14622	83 5/8	15678	88 5/8	16686	93 5/8	17634	98 5/8	18508	103 5/8	19292	108 5/8	19967	113 5/8	20503	118 5/8	20845
68 3/4	12436	73 3/4	13556	78 3/4	14649	83 3/4	15704	88 3/4	16711	93 3/4	17657	98 3/4	18529	103 3/4	19311	108 3/4	19982	113 3/4	20514	118 3/4	20850
68 7/8	12464	73 7/8	13583	78 7/8	14675	83 7/8	15730	88 7/8	16735	93 7/8	17679	98 7/8	18549	103 7/8	19329	108 7/8	19997	113 7/8	20525	118 7/8	20855
69	12492	74	13611	79	14702	84	15755	89	16759	94	17702	99	18570	104	19347	109	20012	114	20536	119	20859
69 1/8	12521	74 1/8	13639	79 1/8	14729	84 1/8	15781	89 1/8	16784	94 1/8	17725	99 1/8	18591	104 1/8	19365	109 1/8	20027	114 1/8	20547	119 1/8	20863
69 1/4	12549	74 1/4	13666	79 1/4	14756	84 1/4	15807	89 1/4	16808	94 1/4	17747	99 1/4	18611	104 1/4	19383	109 1/4	20042	114 1/4	20558	119 1/4	20867
69 3/8	12577	74 3/8	13694	79 3/8	14783	84 3/8	15833	89 3/8	16832	94 3/8	17770	99 3/8	18632	104 3/8	19401	109 3/8	20057	114 3/8	20569	119 3/8	20871
69 1/2	12605	74 1/2	13722	79 1/2	14809	84 1/2	15858	89 1/2	16857	94 1/2	17793	99 1/2	18652	104 1/2	19419	109 1/2	20072	114 1/2	20579	119 1/2	20874
69 5/8	12633	74 5/8	13749	79 5/8	14836	84 5/8	15884	89 5/8	16881	94 5/8	17815	99 5/8	18672	104 5/8	19437	109 5/8	20086	114 5/8	20590	119 5/8	20877
69 3/4	12662	74 3/4	13777	79 3/4	14863	84 3/4	15909	89 3/4	16905	94 3/4	17838	99 3/4	18693	104 3/4	19454	109 3/4	20101	114 3/4	20600	119 3/4	20879
69 7/8	12690	74 7/8	13804	79 7/8	14890	84 7/8	15935	89 7/8	16929	94 7/8	17860	99 7/8	18713	104 7/8	19472	109 7/8	20115	114 7/8	20610	119 7/8	20881
70	12718	75	13832	80	14916	85	15961	90	16953	95	17882	100	18733	105	19490	110	20130	115	20620		
70 1/8	12746	75 1/8	13859	80 1/8	14943	85 1/8	15986	90 1/8	16977	95 1/8	17905	100 1/8	18753	105 1/8	19507	110 1/8	20144	115 1/8	20630		
70 1/4	12774	75 1/4	13887	80 1/4	14970	85 1/4	16011	90 1/4	17001	95 1/4	17927	100 1/4	18773	105 1/4	19525	110 1/4	20158	115 1/4	20640		
70 3/8	12802	75 3/8	13914	80 3/8	14996	85 3/8	16037	90 3/8	17025	95 3/8	17949	100 3/8	18794	105 3/8	19542	110 3/8	20172	115 3/8	20650		
70 1/2	12830	75 1/2	13942	80 1/2	15023	85 1/2	16062	90 1/2	17049	95 1/2	17971	100 1/2	18813	105 1/2	19559	110 1/2	20186	115 1/2	20659		
70 5/8	12858	75 5/8	13969	80 5/8	15049	85 5/8	16088	90 5/8	17073	95 5/8	17993	100 5/8	18833	105 5/8	19577	110 5/8	20200	115 5/8	20668		
70 3/4	12886	75 3/4	13997	80 3/4	15076	85 3/4	16113	90 3/4	17097	95 3/4	18015	100 3/4	18853	105 3/4	19594	110 3/4	20214	115 3/4	20678		
70 7/8	12915	75 7/8	14024	80 7/8	15102	85 7/8	16138	90 7/8	17121	95 7/8	18037	100 7/8	18873	105 7/8	19611	110 7/8	20227	115 7/8	20687		

** PRECISION IS ABOUT +/- 1%