


NN10411417EP

FIBERGLASS TANK





NOTES:
 - GENERIC DRAWING FOR REFERENCE ONLY
 - SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.					2019
TOLERANCES (LINEAR) FEET DIM. -> ± 1% 0.0 -> ± 0.5" 0.00 -> ± 0.25" 0.000 -> ± 0.125"			Revision description		
			Format B	Part no. NN10411417EP	REV 02.
TOLERANCES (ANGULAR) 0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG. 0.00 -> ± 0.1 DEG.		Drawn by O. Marin	19/12/2023		
Weight : 9746 Lb		Approved by :	Title		
Client		# Project	10' Dia. TANK - 37039 US gal		
			Sheet 1 / 4		

Item	Part Number	Qty	Description	Check List
1	ADF0000001	1	FOAM 28-3/4" DIA. x 8" / R-35	
2	ADP0000001	2	LIFTING LUG	
3	ENSCOUR10	9	ANCHORING KIT	
4	EV480	1	4" SCH. 80 VENT KIT WITH SST BIRD SCREEN	
5	GMHE30-COVER01	1	30" DIA. FRP. - LOCKABLE MAN HOLE COVER WITH HINGE	
6	MH-30 (6"L.)	1	30" DIA. x 6" L. - MANHOLE	
7	MHE-30 (54"L.)	1	30" DIA. x 54" L. - MANHOLE EXTENSION	
8	PFV01414	1	0.5" x 13.5" x 13.5" ANTI-VORTEX PLATE	
9	TP80400G01 (4.25"L.)	1	4" SCH.80 GREY PVC PIPE	
10	TP80400G01 (42"L.)	2	4" SCH.80 GREY PVC PIPE	

BACKFILL PROPERTIES
N1 - 1/8" TO 3/4" PEA GRAVEL OR 1/2" CRUSHED STONE
N2 - PRIMARY BACKFILL, 1/8" TO 3/4" PEA GRAVEL OR 1/2" CRUSHED STONE
N3 - SECONDARY BACKFILL, COARSE SAND OR GRAVEL 1 1/2" OR LESS



Optional anchoring depending on the tank's environment

Technical informations


- Burrial depth: According to the geotechnical installation conditions
- Inside Diameter : 120" "
- (If required) Quantity of fiberglass anchoring straps : 9
- (If required) Quantity of reinforced concrete deadman anchors : 18
- Simultaneous lifting by 2 lugs. The angle of the (chains or belts, etc.) must not be less than 60° from the horizontal
- The weight on the drawing does not include kits of belts and concrete blocks.
- HS-20 rated for burial depth from 36 to 84 inches
- Manufactured according to ANSI-AWWA D120 requirements
- Manufactured according to NSF-61 requirements for drinking water
- Airtightness test performed at the factory at 35 kPa

The tank must be installed in accordance with the manufacturer's instructions.

SECTION ELEVATION VIEW

NOTES:
- GENERIC DRAWING FOR REFERENCE ONLY
- SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.					2019
TOLERANCES (LINEAR)			Revision description		
FEET DIM. -> ± 1%			Format B	Part no. NN10411417EP	REV 02.
0.0 -> ± 0.5"					
TOLERANCES (ANGULAR)		Drawn by O. Marin	19/12/2023		
0 -> ± 2 DEG.					
0.0 -> ± 0.5 DEG.					
Weight : 9746 Lb		Approved by :	Title 10' Dia. TANK - 37039 US gal		
Client		# Project	Sheet		2 / 4



PLAN VIEW

NOTES:
- GENERIC DRAWING FOR REFERENCE ONLY
- SHOP DRAWING AVAILABLE ON REQUEST

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019
TOLERANCES (LINEAR) FEET DIM. -> ± 1% 0.0 -> ± 0.5" 0.00 -> ± 0.25" 0.000 -> ± 0.125"			GRANBY COMPOSITES Drawn by O. Marin Approved by :			Revision description				
						Format B	Part no. NN10411417EP		REV 02.	
TOLERANCES (ANGULAR) 0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG. 0.00 -> ± 0.1 DEG.			19/12/2023			Title 10' Dia. TANK - 37039 US gal				
Weight : 9746 Lb										
Client		# Project			Sheet 3 / 4					



ITEM : ENSCOUR10



Fiberglass Strap Guide
Directly installed on the tank

- Turnbuckle**
- Forged carbon steel, hot-dip galvanized
 - In accordance with US specifications FF-T-791B Type 1, Form 1 (open cage).
 - Safety factor 5:1
 - Working load 5,200 Lbs
- Concrete deadman anchor**
- Weight : 1,093 Lbs
 - Reinforced with galvanized steel
- Fiberglass strap**
- High quality fiberglass
 - Working load 20,000 Lbs
 - Ultimate rated 45,000 Lbs
 - Equipped with galvanized steel rings

This drawing is the exclusive property of Granby Composites Inc. No part of this drawing may be used or reproduced in any manner without its written permission.										2019
TOLERANCES (LINEAR)						Revision description				
FEET DIM. -> ± 1% 0.0 -> ± 0.5"						Format B		Part no. ENSCOUR10		REV A.
TOLERANCES (ANGULAR)			Drawn by O. Marin			04/10/2018			Title ANCHORING KIT	
0 -> ± 2 DEG. 0.0 -> ± 0.5 DEG.			0.00 -> ± 0.125" 0.00 -> ± 0.1 DEG.							
Weight :			Approved by :							
Client		# Projet			Sheet 4 / 4					



CAPACITY CHART FOR NN10411417 TANK

Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)
-		6	648	12	1834	18	3354	24	5124	30	7088	36	9204	42	11435	48	13751	54	16122	60	18520
1/8	2	6 1/8	668	12 1/8	1863	18 1/8	3388	24 1/8	5163	30 1/8	7130	36 1/8	9249	42 1/8	11483	48 1/8	13800	54 1/8	16172	60 1/8	18570
1/4	6	6 1/4	689	12 1/4	1891	18 1/4	3423	24 1/4	5202	30 1/4	7173	36 1/4	9294	42 1/4	11530	48 1/4	13849	54 1/4	16221	60 1/4	18620
3/8	10	6 3/8	710	12 3/8	1920	18 3/8	3458	24 3/8	5241	30 3/8	7216	36 3/8	9340	42 3/8	11578	48 3/8	13898	54 3/8	16271	60 3/8	18670
1/2	16	6 1/2	731	12 1/2	1949	18 1/2	3493	24 1/2	5281	30 1/2	7259	36 1/2	9386	42 1/2	11625	48 1/2	13947	54 1/2	16321	60 1/2	18720
5/8	22	6 5/8	752	12 5/8	1979	18 5/8	3528	24 5/8	5320	30 5/8	7302	36 5/8	9431	42 5/8	11673	48 5/8	13996	54 5/8	16371	60 5/8	18770
3/4	29	6 3/4	774	12 3/4	2008	18 3/4	3563	24 3/4	5359	30 3/4	7345	36 3/4	9477	42 3/4	11721	48 3/4	14045	54 3/4	16421	60 3/4	18820
7/8	36	6 7/8	795	12 7/8	2037	18 7/8	3598	24 7/8	5399	30 7/8	7388	36 7/8	9523	42 7/8	11768	48 7/8	14094	54 7/8	16470	60 7/8	18870
1	44	7	817	13	2067	19	3633	25	5439	31	7431	37	9568	43	11816	49	14143	55	16520	61	18920
1 1/8	52	7 1/8	839	13 1/8	2097	19 1/8	3669	25 1/8	5479	31 1/8	7474	37 1/8	9614	43 1/8	11864	49 1/8	14192	55 1/8	16570	61 1/8	18970
1 1/4	61	7 1/4	861	13 1/4	2127	19 1/4	3704	25 1/4	5518	31 1/4	7517	37 1/4	9660	43 1/4	11912	49 1/4	14241	55 1/4	16620	61 1/4	19020
1 3/8	71	7 3/8	884	13 3/8	2157	19 3/8	3740	25 3/8	5558	31 3/8	7561	37 3/8	9706	43 3/8	11960	49 3/8	14290	55 3/8	16670	61 3/8	19070
1 1/2	81	7 1/2	906	13 1/2	2187	19 1/2	3775	25 1/2	5598	31 1/2	7604	37 1/2	9752	43 1/2	12007	49 1/2	14340	55 1/2	16720	61 1/2	19120
1 5/8	91	7 5/8	929	13 5/8	2217	19 5/8	3811	25 5/8	5638	31 5/8	7647	37 5/8	9798	43 5/8	12055	49 5/8	14389	55 5/8	16770	61 5/8	19170
1 3/4	102	7 3/4	952	13 3/4	2247	19 3/4	3847	25 3/4	5678	31 3/4	7691	37 3/4	9844	43 3/4	12103	49 3/4	14438	55 3/4	16820	61 3/4	19220
1 7/8	113	7 7/8	975	13 7/8	2278	19 7/8	3883	25 7/8	5719	31 7/8	7734	37 7/8	9890	43 7/8	12151	49 7/8	14487	55 7/8	16869	61 7/8	19270
2	124	8	999	14	2309	20	3919	26	5759	32	7778	38	9936	44	12199	50	14537	56	16919	62	19320
2 1/8	136	8 1/8	1022	14 1/8	2339	20 1/8	3955	26 1/8	5799	32 1/8	7822	38 1/8	9982	44 1/8	12247	50 1/8	14586	56 1/8	16969	62 1/8	19370
2 1/4	148	8 1/4	1046	14 1/4	2370	20 1/4	3992	26 1/4	5840	32 1/4	7865	38 1/4	10029	44 1/4	12295	50 1/4	14635	56 1/4	17019	62 1/4	19420
2 3/8	161	8 3/8	1070	14 3/8	2401	20 3/8	4028	26 3/8	5880	32 3/8	7909	38 3/8	10075	44 3/8	12344	50 3/8	14684	56 3/8	17069	62 3/8	19470
2 1/2	174	8 1/2	1094	14 1/2	2432	20 1/2	4064	26 1/2	5921	32 1/2	7953	38 1/2	10121	44 1/2	12392	50 1/2	14734	56 1/2	17119	62 1/2	19520
2 5/8	187	8 5/8	1118	14 5/8	2464	20 5/8	4101	26 5/8	5962	32 5/8	7997	38 5/8	10168	44 5/8	12440	50 5/8	14783	56 5/8	17169	62 5/8	19570
2 3/4	200	8 3/4	1143	14 3/4	2495	20 3/4	4138	26 3/4	6003	32 3/4	8041	38 3/4	10214	44 3/4	12488	50 3/4	14832	56 3/4	17219	62 3/4	19620
2 7/8	214	8 7/8	1167	14 7/8	2527	20 7/8	4175	26 7/8	6043	32 7/8	8085	38 7/8	10260	44 7/8	12536	50 7/8	14882	56 7/8	17269	62 7/8	19670
3	228	9	1192	15	2558	21	4211	27	6084	33	8129	39	10307	45	12584	51	14931	57	17319	63	19720
3 1/8	243	9 1/8	1217	15 1/8	2590	21 1/8	4248	27 1/8	6125	33 1/8	8173	39 1/8	10354	45 1/8	12633	51 1/8	14981	57 1/8	17369	63 1/8	19770
3 1/4	258	9 1/4	1242	15 1/4	2622	21 1/4	4285	27 1/4	6166	33 1/4	8217	39 1/4	10400	45 1/4	12681	51 1/4	15030	57 1/4	17419	63 1/4	19820
3 3/8	273	9 3/8	1267	15 3/8	2654	21 3/8	4323	27 3/8	6207	33 3/8	8262	39 3/8	10447	45 3/8	12729	51 3/8	15080	57 3/8	17469	63 3/8	19870
3 1/2	288	9 1/2	1293	15 1/2	2686	21 1/2	4360	27 1/2	6249	33 1/2	8306	39 1/2	10493	45 1/2	12778	51 1/2	15129	57 1/2	17519	63 1/2	19920
3 5/8	304	9 5/8	1318	15 5/8	2719	21 5/8	4397	27 5/8	6290	33 5/8	8350	39 5/8	10540	45 5/8	12826	51 5/8	15179	57 5/8	17569	63 5/8	19970
3 3/4	319	9 3/4	1344	15 3/4	2751	21 3/4	4435	27 3/4	6331	33 3/4	8395	39 3/4	10587	45 3/4	12875	51 3/4	15228	57 3/4	17619	63 3/4	20020
3 7/8	336	9 7/8	1370	15 7/8	2784	21 7/8	4472	27 7/8	6373	33 7/8	8439	39 7/8	10634	45 7/8	12923	51 7/8	15278	57 7/8	17669	63 7/8	20070
4	352	10	1396	16	2816	22	4510	28	6414	34	8484	40	10680	46	12972	52	15327	58	17719	64	20120
4 1/8	369	10 1/8	1422	16 1/8	2849	22 1/8	4547	28 1/8	6456	34 1/8	8528	40 1/8	10727	46 1/8	13020	52 1/8	15377	58 1/8	17769	64 1/8	20170
4 1/4	386	10 1/4	1449	16 1/4	2882	22 1/4	4585	28 1/4	6497	34 1/4	8573	40 1/4	10774	46 1/4	13069	52 1/4	15426	58 1/4	17819	64 1/4	20220
4 3/8	403	10 3/8	1475	16 3/8	2915	22 3/8	4623	28 3/8	6539	34 3/8	8618	40 3/8	10821	46 3/8	13117	52 3/8	15476	58 3/8	17869	64 3/8	20270
4 1/2	420	10 1/2	1502	16 1/2	2948	22 1/2	4661	28 1/2	6581	34 1/2	8662	40 1/2	10868	46 1/2	13166	52 1/2	15525	58 1/2	17919	64 1/2	20319
4 5/8	438	10 5/8	1529	16 5/8	2981	22 5/8	4699	28 5/8	6623	34 5/8	8707	40 5/8	10915	46 5/8	13214	52 5/8	15575	58 5/8	17969	64 5/8	20369
4 3/4	456	10 3/4	1556	16 3/4	3014	22 3/4	4737	28 3/4	6665	34 3/4	8752	40 3/4	10962	46 3/4	13263	52 3/4	15625	58 3/4	18019	64 3/4	20419
4 7/8	474	10 7/8	1583	16 7/8	3048	22 7/8	4776	28 7/8	6707	34 7/8	8797	40 7/8	11009	46 7/8	13312	52 7/8	15674	58 7/8	18069	64 7/8	20469
5	493	11	1610	17	3081	23	4814	29	6749	35	8842	41	11057	47	13360	53	15724	59	18119	65	20519
5 1/8	511	11 1/8	1638	17 1/8	3115	23 1/8	4852	29 1/8	6791	35 1/8	8887	41 1/8	11104	47 1/8	13409	53 1/8	15774	59 1/8	18169	65 1/8	20569
5 1/4	530	11 1/4	1665	17 1/4	3149	23 1/4	4891	29 1/4	6833	35 1/4	8932	41 1/4	11151	47 1/4	13458	53 1/4	15823	59 1/4	18219	65 1/4	20619
5 3/8	549	11 3/8	1693	17 3/8	3183	23 3/8	4929	29 3/8	6875	35 3/8	8977	41 3/8	11198	47 3/8	13507	53 3/8	15873	59 3/8	18269	65 3/8	20668
5 1/2	569	11 1/2	1721	17 1/2	3217	23 1/2	4968	29 1/2	6918	35 1/2	9022	41 1/2	11246	47 1/2	13556	53 1/2	15923	59 1/2	18319	65 1/2	20718
5 5/8	588	11 5/8	1749	17 5/8	3251	23 5/8	5007	29 5/8	6960	35 5/8	9068	41 5/8	11293	47 5/8	13604	53 5/8	15972	59 5/8	18369	65 5/8	20768
5 3/4	608	11 3/4	1777	17 3/4	3285	23 3/4	5046	29 3/4	7003	35 3/4	9113	41 3/4	11340	47 3/4	13653	53 3/4	16022	59 3/4	18419	65 3/4	20818
5 7/8	628	11 7/8	1805	17 7/8	3319	23 7/8	5085	29 7/8	7045	35 7/8	9158	41 7/8	11388	47 7/8	13702	53 7/8	16072	59 7/8	18470	65 7/8	20868

** PRECISION IS ABOUT +/- 1%



CAPACITY CHART FOR NN10411417 TANK

Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)	Height (in)	Gallons (U.S.)
66	20917	71	22896	76	24840	81	26732	86	28555	91	30290	96	31916	101	33406	106	34731	111	35847	116	36687
66 1/8	20967	71 1/8	22945	76 1/8	24888	81 1/8	26779	86 1/8	28600	91 1/8	30332	96 1/8	31955	101 1/8	33441	106 1/8	34761	111 1/8	35872	116 1/8	36704
66 1/4	21017	71 1/4	22994	76 1/4	24936	81 1/4	26825	86 1/4	28644	91 1/4	30374	96 1/4	31993	101 1/4	33476	106 1/4	34792	111 1/4	35897	116 1/4	36720
66 3/8	21067	71 3/8	23043	76 3/8	24984	81 3/8	26872	86 3/8	28689	91 3/8	30416	96 3/8	32032	101 3/8	33512	106 3/8	34822	111 3/8	35921	116 3/8	36736
66 1/2	21116	71 1/2	23092	76 1/2	25032	81 1/2	26918	86 1/2	28733	91 1/2	30458	96 1/2	32071	101 1/2	33546	106 1/2	34852	111 1/2	35945	116 1/2	36751
66 5/8	21166	71 5/8	23141	76 5/8	25080	81 5/8	26964	86 5/8	28777	91 5/8	30500	96 5/8	32110	101 5/8	33581	106 5/8	34883	111 5/8	35969	116 5/8	36767
66 3/4	21216	71 3/4	23190	76 3/4	25127	81 3/4	27011	86 3/4	28822	91 3/4	30542	96 3/4	32148	101 3/4	33616	106 3/4	34913	111 3/4	35993	116 3/4	36782
66 7/8	21265	71 7/8	23239	76 7/8	25175	81 7/8	27057	86 7/8	28866	91 7/8	30583	96 7/8	32187	101 7/8	33651	106 7/8	34943	111 7/8	36017	116 7/8	36796
67	21315	72	23288	77	25223	82	27103	87	28910	92	30625	97	32225	102	33685	107	34972	112	36040	117	36811
67 1/8	21365	72 1/8	23337	77 1/8	25271	82 1/8	27149	87 1/8	28954	92 1/8	30666	97 1/8	32264	102 1/8	33720	107 1/8	35002	112 1/8	36064	117 1/8	36825
67 1/4	21414	72 1/4	23386	77 1/4	25318	82 1/4	27195	87 1/4	28998	92 1/4	30708	97 1/4	32302	102 1/4	33754	107 1/4	35031	112 1/4	36087	117 1/4	36839
67 3/8	21464	72 3/8	23435	77 3/8	25366	82 3/8	27241	87 3/8	29042	92 3/8	30749	97 3/8	32340	102 3/8	33788	107 3/8	35061	112 3/8	36110	117 3/8	36852
67 1/2	21514	72 1/2	23484	77 1/2	25414	82 1/2	27287	87 1/2	29086	92 1/2	30790	97 1/2	32378	102 1/2	33822	107 1/2	35090	112 1/2	36133	117 1/2	36866
67 5/8	21563	72 5/8	23532	77 5/8	25461	82 5/8	27333	87 5/8	29130	92 5/8	30832	97 5/8	32416	102 5/8	33856	107 5/8	35119	112 5/8	36155	117 5/8	36878
67 3/4	21613	72 3/4	23581	77 3/4	25509	82 3/4	27379	87 3/4	29174	92 3/4	30873	97 3/4	32454	102 3/4	33890	107 3/4	35148	112 3/4	36178	117 3/4	36891
67 7/8	21662	72 7/8	23630	77 7/8	25556	82 7/8	27425	87 7/8	29217	92 7/8	30914	97 7/8	32492	102 7/8	33924	107 7/8	35177	112 7/8	36200	117 7/8	36903
68	21712	73	23679	78	25604	83	27471	88	29261	93	30955	98	32529	103	33958	108	35205	113	36222	118	36915
68 1/8	21762	73 1/8	23727	78 1/8	25651	83 1/8	27517	88 1/8	29305	93 1/8	30996	98 1/8	32567	103 1/8	33991	108 1/8	35234	113 1/8	36244	118 1/8	36927
68 1/4	21811	73 1/4	23776	78 1/4	25699	83 1/4	27562	88 1/4	29348	93 1/4	31037	98 1/4	32605	103 1/4	34025	108 1/4	35262	113 1/4	36266	118 1/4	36938
68 3/8	21861	73 3/8	23825	78 3/8	25746	83 3/8	27608	88 3/8	29392	93 3/8	31077	98 3/8	32642	103 3/8	34058	108 3/8	35290	113 3/8	36287	118 3/8	36948
68 1/2	21910	73 1/2	23873	78 1/2	25794	83 1/2	27654	88 1/2	29435	93 1/2	31118	98 1/2	32679	103 1/2	34091	108 1/2	35318	113 1/2	36308	118 1/2	36959
68 5/8	21960	73 5/8	23922	78 5/8	25841	83 5/8	27699	88 5/8	29479	93 5/8	31159	98 5/8	32717	103 5/8	34124	108 5/8	35346	113 5/8	36329	118 5/8	36968
68 3/4	22009	73 3/4	23970	78 3/4	25888	83 3/4	27745	88 3/4	29522	93 3/4	31199	98 3/4	32754	103 3/4	34157	108 3/4	35374	113 3/4	36350	118 3/4	36978
68 7/8	22058	73 7/8	24019	78 7/8	25935	83 7/8	27790	88 7/8	29565	93 7/8	31240	98 7/8	32791	103 7/8	34190	108 7/8	35402	113 7/8	36371	118 7/8	36987
69	22108	74	24068	79	25983	84	27836	89	29608	94	31280	99	32828	104	34223	109	35429	114	36391	119	36995
69 1/8	22157	74 1/8	24116	79 1/8	26030	84 1/8	27881	89 1/8	29651	94 1/8	31320	99 1/8	32865	104 1/8	34256	109 1/8	35456	114 1/8	36411	119 1/8	37003
69 1/4	22207	74 1/4	24165	79 1/4	26077	84 1/4	27926	89 1/4	29694	94 1/4	31361	99 1/4	32901	104 1/4	34288	109 1/4	35484	114 1/4	36431	119 1/4	37010
69 3/8	22256	74 3/8	24213	79 3/8	26124	84 3/8	27972	89 3/8	29737	94 3/8	31401	99 3/8	32938	104 3/8	34321	109 3/8	35511	114 3/8	36451	119 3/8	37017
69 1/2	22305	74 1/2	24261	79 1/2	26171	84 1/2	28017	89 1/2	29780	94 1/2	31441	99 1/2	32975	104 1/2	34353	109 1/2	35537	114 1/2	36471	119 1/2	37023
69 5/8	22355	74 5/8	24310	79 5/8	26218	84 5/8	28062	89 5/8	29823	94 5/8	31481	99 5/8	33011	104 5/8	34385	109 5/8	35564	114 5/8	36490	119 5/8	37029
69 3/4	22404	74 3/4	24358	79 3/4	26265	84 3/4	28107	89 3/4	29866	94 3/4	31521	99 3/4	33048	104 3/4	34417	109 3/4	35591	114 3/4	36509	119 3/4	37033
69 7/8	22453	74 7/8	24406	79 7/8	26312	84 7/8	28152	89 7/8	29909	94 7/8	31561	99 7/8	33084	104 7/8	34449	109 7/8	35617	114 7/8	36528	119 7/8	37037
70	22503	75	24455	80	26359	85	28197	90	29951	95	31600	100	33120	105	34481	110	35643	115	36547		
70 1/8	22552	75 1/8	24503	80 1/8	26405	85 1/8	28242	90 1/8	29994	95 1/8	31640	100 1/8	33156	105 1/8	34512	110 1/8	35669	115 1/8	36565		
70 1/4	22601	75 1/4	24551	80 1/4	26452	85 1/4	28287	90 1/4	30037	95 1/4	31680	100 1/4	33192	105 1/4	34544	110 1/4	35695	115 1/4	36583		
70 3/8	22650	75 3/8	24599	80 3/8	26499	85 3/8	28332	90 3/8	30079	95 3/8	31719	100 3/8	33228	105 3/8	34575	110 3/8	35721	115 3/8	36601		
70 1/2	22699	75 1/2	24648	80 1/2	26546	85 1/2	28377	90 1/2	30121	95 1/2	31759	100 1/2	33264	105 1/2	34607	110 1/2	35747	115 1/2	36619		
70 5/8	22749	75 5/8	24696	80 5/8	26592	85 5/8	28421	90 5/8	30164	95 5/8	31798	100 5/8	33300	105 5/8	34638	110 5/8	35772	115 5/8	36636		
70 3/4	22798	75 3/4	24744	80 3/4	26639	85 3/4	28466	90 3/4	30206	95 3/4	31837	100 3/4	33335	105 3/4	34669	110 3/4	35797	115 3/4	36653		
70 7/8	22847	75 7/8	24792	80 7/8	26686	85 7/8	28511	90 7/8	30248	95 7/8	31876	100 7/8	33371	105 7/8	34700	110 7/8	35822	115 7/8	36670		

** PRECISION IS ABOUT +/- 1%